NOT A BID FORM



CT CONSULTANTS CITY OF SOUTHGATE

	Project:	NORTH STREET STABILIZATION PROJECT	Date: Project No.:	5/30/2019 190500
ITEM NO.	SPEC. NO.	ITEM	Estimated Quantity	Unit of Measure
1	110	MOBILIZATION	1	LS
2	112	MAINTENANCE OF TRAFFIC	1	LS
3	202	CLEARING & GRUBBING (includes the removal & reinstallation of signs & mailboxes)	1	LS
4	203	REMOVE EXISTING PAVEMENT	120	SY
5	207	SUBGRADE RESHAPING & COMPACTING	120	SY
6	212/213	EROSION & WATER POLLUTION CONTROL	1	LS
7	SPL	YARD RESTORATION (4" TOPSOIL, SEED & MULCH)	200	SY
8	302	KTC DENSE GRADED AGGREGATE	90	CY
9	402/403	ASPHALT PAVEMENT SURFACE COURSE (2")	10	CY
10	SPL	DRILLED SHAFT WALL BASE BID. INSTALL THE DRILLED SHAFT WALL, INCLUDING PLUGS, WOOD LAGGING, CONTROLLED BACKFILL, , PER THE PROJECT SPECIFICATIONS AND THE GENERAL NOTES, PLANS, DETAILS & SECTIONS ON DRAWINGS 101, 102, 103, 104, 105 AND 106 (PREPARED BY GEOTECHNOLOGY, INC. DATED 4-29-19) COMPLETE WITH MOBILIZATION, MATERIALS, LABOR, EQUIPMENT & MANAGEMENT	1	LS
		TOTAL BASE BID		

NOT A BID FORM



CT CONSULTANTS CITY OF SOUTHGATE

Project:	NORTH STREET STABILIZATION PROJECT	Date: Project No.:	5/30/2019 190500
SPEC. NO.	TEM	Estimated Quantity	Unit of Measure
SPL	ADJUSTMENTS FROM TOTAL COMPLETED DRILLED SHAFT FOOTAGE FOR 24" DIAMETER REINFORCED DRILLED SHAFT (291L.F.) RELATED TO ITEM 10.	ADD	\$/L.F.
		DEDUÇT	\$/L.F.
SPL.	ADJUSTMENTS FROM TOTAL COMPLETED DRILLED SHAFT	ADD	\$/L.F.
	FOOTAGE FOR 30" DIAMETER REINFORCED DRILLED SHAFT (392 L.F.) RELATED TO ITEM 10.	DEDUCT	\$/L.F.
	SPEC. NO. SPL	SPEC: ITEM SPL ADJUSTMENTS FROM TOTAL COMPLETED DRILLED SHAFT FOOTAGE FOR 24" DIAMETER REINFORCED DRILLED SHAFT (291L.F.) RELATED TO ITEM 10. SPL ADJUSTMENTS FROM TOTAL COMPLETED DRILLED SHAFT FOOTAGE FOR 30" DIAMETER REINFORCED DRILLED SHAFT (392)	SPEC. SPEC. SPEC. ADJUSTMENTS FROM TOTAL COMPLETED DRILLED SHAFT (291L.F.) RELATED TO ITEM 10. SPL ADJUSTMENTS FROM TOTAL COMPLETED DRILLED SHAFT (291L.F.) RELATED TO ITEM 10. SPL ADJUSTMENTS FROM TOTAL COMPLETED DRILLED SHAFT FOOTAGE FOR 30" DIAMETER REINFORCED DRILLED SHAFT FOOTAGE FOR 30" DIAMETER REINFORCED DRILLED SHAFT (392